

View Online at <https://aerobasegroup.com/nsn/5305-01-384-1672>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.641 inches

**Fastener Length:**

Between 4.064 inches and 4.110 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.752 inches and 0.762 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Single Shear Strength:**

10500 pounds per square inch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.375 inches

**Grip Length:**

3.438 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

12700 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams6414 assn standard 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas336 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.