

View Online at <https://aerobasegroup.com/nsn/5305-01-384-2101>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.489 inches and 0.589 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.480 inches and 0.531 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.156 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

155000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 84.0 degrees

**Surface Finish:**

32.0 microinches fastener

**Color:**

Black

**Material:**

Nickel alloy 400

**Material Specification:**

Qq-n-281 cla federal specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

4 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.