NSN 5305-01-384-7389

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-384-7389 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.593 inches **Fastener Length:** Between 0.609 inches and 0.626 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416. Ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1801 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

NSN 5305-01-384-7389

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.