NSN 5305-01-385-2001

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-385-2001 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.375 inches **Fastener Length:** 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **First Diameter From Head:** 0.151 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Material Specification:

66 federal standard 1st material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 2nd material response or 66 federal standard 5th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-385-2001

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unrf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0