NSN 5305-01-385-2322

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-385-2322

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.250 inches
Fastener Length:
2.560 inches
Head Style:
Knurled no. 4
Head Diameter:
0.680 inches
Head Height:
0.630 inches
Hole Diameter:
Between 0.069 inches and 0.074 inches
Thread Diameter:
0.190 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round
Special Features:
0.045 in. Min and 0.050 in. Maximum hole in shank, 0.130 in.Dnnnn distance in threaded end
Material:
Steel comp xm-12
Material Specification:
Ams 5659 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Thread Series Designator:

Unjf

NSN 5305-01-385-2322

Thumbscrew - Page 2 of 2



Shelf L	ife:
---------	------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.