NSN 5305-01-385-3846

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-385-3846 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.146 inches and 0.166 inches **Fastener Length:** Between 0.423 inches and 0.453 inches **Head Style:** Fillister **Head Diameter:** Between 0.120 inches and 0.130 inches **Head Height:** Between 0.068 inches and 0.083 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.365 inches and 0.385 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-385-3846

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072-e300 spec.