NSN 5305-01-385-5695

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-385-5695

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| Between 0.251 inches and 0.301 inches |
| Fastener Length: |
| Between 0.699 inches and 0.729 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.306 inches and 0.313 inches |
| Head Height: |
| Between 0.103 inches and 0.118 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5737 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type ii, class 2 federal specification all treatment responses |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1123 professional/industrial association standard |
| Shelf Life: |
| N/a |
| |

NSN 5305-01-385-5695

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

