

View Online at <https://aerobasegroup.com/nsn/5305-01-385-5889>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

Between 0.427 inches and 0.447 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.261 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

0.161 inches

**Features Provided:**

Cetyl alcohol lubricant

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Minimum Yield Strength:**

95000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Color:**

Bronze

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5652 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5652 spec.