

View Online at <https://aerobasegroup.com/nsn/5305-01-385-5889>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.312 inches

Fastener Length:

Between 0.427 inches and 0.447 inches

Head Style:

Flat countersunk

Head Diameter:

0.261 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

0.161 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

95000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Color:

Bronze

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5652 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5652 spec.