NSN 5305-01-385-9816

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-385-9816

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| 6.6 millimeters |
| Fastener Length: |
| Between 9.5 millimeters and 10.0 millimeters |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 3.90 millimeters and 4.40 millimeters |
| Locking Feature: |
| Patch |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 2.2 millimeters |
| Thread Pitch In Millimeters: |
| 0.45 |
| External Thread Tolerance Class: |
| 6g |
| Countersink Angle: |
| Between 90.0 degrees and 92.0 degrees |
| Screw Material: |
| Steel |
| Locking Feature Material: |
| Plastic polyamide |
| Screw Material Specification: |
| Qq-s-763 federal specification single material response and fed-std-66 federal specification single material response |
| Locking Feature Material Specification: |
| L-p-410 federal specification single material response |
| Bearing Surface Of Head Surface Treatment: |
| Passivate |
| Screw Surface Treatment: |
| Passivate |
| Bearing Surface Of Head Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| M |
| Shelf Life: |

N/a

NSN 5305-01-385-9816

Machine Screw - Page 2 of 2



| | | | ıre: |
|--|--|--|------|
| | | | |

--

Demilitarization:

No

Fiig:

A500d0