NSN 5305-01-386-6012

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-386-6012 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.563 inches and 0.625 inches **Fastener Length:** Between 0.593 inches and 0.623 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch Material: Stainless steel fastener **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification 15th treatment response fastener **Thread Series Designator:** Unrf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-386-6012

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.