

View Online at <https://aerobasegroup.com/nsn/5305-01-386-6086>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.000 inches

**Fastener Length:**

Between 0.970 inches and 1.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.720 inches and 0.781 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

0.219 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 45.0 rockwell c

**Countersink Angle:**

Between 80.0 degrees and 84.0 degrees

**Criticality Code Justification:**

Feat

**Special Features:**

This item is flight safety critical. Thread is safety critical per mil-s-7742 under application category safety critical. Apply one coat of mil-p-23377, type 1, cl 1 or 3 and two top coats of mil-c-46168, color code 33538 per fed-std-595 to top of head.

**Material:**

Steel

**Material Specification:**

Fed-std66 federal standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0