## NSN 5305-01-387-3068

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-387-3068 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** Between 0.344 inches and 0.406 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.255 inches and 0.275 inches **Head Height:** Between 0.071 inches and 0.083 inches **First Diameter From Head:** Between 0.094 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.235 inches and 0.265 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Stainless steel fastener **Material Specification:** Qq-s-763 300 series federal specification single material response fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-387-3068

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-r-83248 spec.