NSN 5305-01-387-6952

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-387-6952 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.312 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Pacer dawn **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 316 **Screw Material Specification:** Fed standard 66 federal standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Put application of loctite dri-loc201 on the threaded portion only, also altered item drawing **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-387-6952 Machine Screw - Page 2 of 2



Fiig:

A500d0