NSN 5305-01-387-6961



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-387-6961 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.335 inches and 0.355 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Internal Drive Style:** Hexagon **End Application:** Pacer dawn **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.0937 inches and 0.0952 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Altered item, also includes an insulation sleeving thermal, the length iso.120 in. after shrinking will fit over the grip diam. Of min. 0.078and max. Of 0.080 in Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard 1st material response and ams5737 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-387-6961

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0