NSN 5305-01-387-7454

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-387-7454

Thread Class:
3a Thread Birections
Thread Direction:
Right-hand Thread Longth:
Thread Length: 0.276 inches
Fastener Length: Between 0.949 inches and 0.979 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.246 inches and 0.280 inches
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Cross recess type 1
End Application:
Global hawk, rq-4a
Thread Diameter:
0.138 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5305-01-387-7454

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0