## NSN 5305-01-387-9407

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-387-9407 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.648 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Locking Feature:** Patch threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 38.0 rockwell c fastener and 45.0 rockwell c fastener Minimum Yield Strength: 150000 pounds per square inch Color: Bronze fastener or olive drab fastener Material: Steel fastener **Surface Treatment:** Zinc fastener and chromate fastener **Surface Treatment Specification:** 171, 1.9.2.3 military standard single treatment response fastener **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-01-387-9407

Socket Head Cap Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0