

View Online at <https://aerobasegroup.com/nsn/5305-01-387-9407>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.648 inches and 0.750 inches

**Fastener Length:**

Between 0.719 inches and 0.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.365 inches and 0.375 inches

**Head Height:**

Between 0.244 inches and 0.250 inches

**Locking Feature:**

Patch threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.1875 inches and 0.1900 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c fastener and 45.0 rockwell c fastener

**Minimum Yield Strength:**

150000 pounds per square inch

**Color:**

Bronze fastener or olive drab fastener

**Material:**

Steel fastener

**Surface Treatment:**

Zinc fastener and chromate fastener

**Surface Treatment Specification:**

171, 1.9.2.3 military standard single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0