## NSN 5305-01-388-1804



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-388-1804 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.857 inches and 2.000 inches **Fastener Length:** Between 1.940 inches and 2.000 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: 0.614 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Screw Material Specification:** Fed 66 federal standard all material responses **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Mil-std-171, 1.9.2.3 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-std-171 spec.

Mil-std (military Standard):

Fiig: A500d0