

View Online at <https://aerobasegroup.com/nsn/5305-01-388-2309>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.531 inches and 0.625 inches

Fastener Length:

Between 0.593 inches and 0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Internal Drive Style:

Hexagon

End Application:

Mrap - m-atv with cs13 pop and sne

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Color:

Bronze or olive drab

Material:

Steel

Material Specification:

Fed 66 federal standard all material responses

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Mil-std-171, 1.9.2.3 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.