NSN 5305-01-388-2366



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-388-2366 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.637 inches and 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: 0.340 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Screw Material Specification:** Fed66 federal standard all material responses **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Mil-std-171, 1.9.2.3 military specification single treatment response Color: Bronze or olive drab **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-388-2366

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-std-171 spec.