

View Online at <https://aerobasegroup.com/nsn/5305-01-388-2366>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.637 inches and 0.750 inches

Fastener Length:

0.750 inches

Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

Width Between Flats:

0.340 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022

Screw Material Specification:

Fed66 federal standard all material responses

Screw Surface Treatment:

Zinc and chromate

Screw Surface Treatment Specification:

Mil-std-171, 1.9.2.3 military specification single treatment response

Color:

Bronze or olive drab

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-std-171 spec.