

View Online at <https://aerobasegroup.com/nsn/5305-01-388-4441>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.929 inches and 1.000 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Oval

**Head Diameter:**

Between 0.419 inches and 0.437 inches

**Head Height:**

Between 0.122 inches and 0.132 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.156 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 43.0 rockwell c

**Color:**

Black

**Material:**

Steel fastener

**Material Specification:**

Astm f835 assn standard single material response fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response fastener

**Thread Series Designator:**

Unrf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.