NSN 5305-01-388-5058

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-388-5058 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.750 inches and 0.938 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches **First Diameter From Head:** Between 0.218 inches and 0.222 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.100 inches and 0.110 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-388-5058

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0