NSN 5305-01-388-5221

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-388-5221 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.107 inches and 1.250 inches **Fastener Length:** Between 1.190 inches and 1.250 inches **Head Style:** Hexagon **Head Height:** Between 0.208 inches and 0.230 inches Width Between Flats: Between 0.409 inches and 0.500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Screw Material Specification:** Fed 66 federal standard all material responses **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Mil-std-171, 1.9.2.3 military specification single treatment response Bronze and olive drab **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-01-388-5221

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-std-171 spec.