## NSN 5305-01-388-5738

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-388-5738

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.532 inches and 0.594 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Internal Drive Style:
Hexagon
End Application:
Mrap - m-atv with cs13 pop and sne
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.140 inches and 0.142 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Color:
Bronze and olive drab
Material:
Steel
Material Specification:
Fed 66 federal standard all material responses
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Mil-std-171, 1.9.2.3 military specification single treatment response
Thread Series Designator:
Unc

Unc

## NSN 5305-01-388-5738

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-std-171 spec.

Shelf Life: