NSN 5305-01-389-2528

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-2528 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.675 inches and 0.740 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.625 inches and 0.631 inches Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-389-2528

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0