NSN 5305-01-389-2555

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-2555 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.419 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Bronze and olive drab Material: Steel **Material Specification:** Fed 66 federal standard all material responses **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Mil-std-171, 1.9.2.3 military specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-389-2555

Socket Head Cap Screw - Page 2 of 2



	- : -	~	NA	
UI	nit	UΤ	Measure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.