NSN 5305-01-389-3438

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-3438 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Hole Diameter:** Between 0.044 inches and 0.055 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Hole Configuration Style:** Round internal hexagon **Special Features:** Head may or may not be knurled at manufacturers option Color: Bronze and olive drab

Material: Steel

NSN 5305-01-389-3438

Mil-std (military Standard):

Mil-std-171 spec.

Socket Head Cap Screw - Page 2 of 2



Material Specification:
Fed 66 federal standard all material responses
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Mil-std-171, 1.9.2.3 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0