NSN 5305-01-389-3472

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-3472

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.544 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Locking Feature:
Patch threads or strip threads
Internal Drive Style:
Hexagon Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
39.0 rockwell c fastener and 45.0 rockwell c fastener
Minimum Yield Strength:
155000 pounds per square inch
Color:
Bronze fastener and olive drab fastener
Material:
Steel fastener
Material Specification:
Fed 66 federal standard all material responses fastener
Surface Treatment:
Zinc fastener and chromate fastener
Surface Treatment Specification:
Mil-std-171, 1.9.2.3 military specification single treatment response fastener
Thread Series Designator:
Unf

Unf

NSN 5305-01-389-3472

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
No Fiig:	

Mil-std (military Standard):

Mil-std-171 spec.

Shelf Life: