NSN 5305-01-389-4170

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-4170 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.067 inches and 1.250 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.468 inches **Head Height:** Between 0.306 inches and 0.312 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Bronze and olive drab Material: Steel **Material Specification:** Fed 66 federal standard all material responses **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Mil-std-171, 1.9.2.3 military specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-01-389-4170

Socket Head Cap Screw - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.