NSN 5305-01-389-4192

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-4192 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.898 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Bronze and olive drab Material: Steel **Material Specification:** Fed 66 federal standard all material responses **Surface Treatment:** Mil-std-171, 1.9.2.3 military specification single treatment response

Zinc and chromate **Surface Treatment Specification: Thread Series Designator:** Unf Shelf Life: N/a

NSN 5305-01-389-4192

Socket Head Cap Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.