NSN 5305-01-389-5956

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-5956 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.875 inches **Head Style:** Flat countersunk **Head Diameter:** 0.531 inches **Locking Feature:** Patch threads **First Diameter From Head:** 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.339 inches **Point Style:** Flat **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 316 **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-389-5956

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-18240 spec.