NSN 5305-01-389-5991

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-5991

Thread Class: 2a **Thread Direction:** Right-hand Thread Length: 0.160 inches **Fastener Length:** 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.114 inches and 0.138 inches **Second Diameter From Head:** Between 0.096 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.050 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.340 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 316 **Material Specification:** Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a380 assn standard single treatment response

Thread Series Designator:

Unc

NSN 5305-01-389-5991

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0