Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-6372

Thread Class: Ja Thread Direction: Right-hand Thread Length: 1.250 inches Fastener Length: Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches
Thread Direction: Right-hand Thread Length: 1.250 inches Fastener Length: Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Right-hand Thread Length: 1.250 inches Fastener Length: Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Thread Length: 1.250 inches Fastener Length: Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches
1.250 inches Fastener Length: Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Fastener Length: Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Between 1.960 inches and 2.000 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Head Height: Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Between 0.368 inches and 0.375 inches Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Internal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Hexagon Thread Diameter: 0.375 inches Width Across Flats:
Thread Diameter: 0.375 inches Width Across Flats:
0.375 inches Width Across Flats:
Width Across Flats:
Between 0.3125 inches and 0.3160 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 42.0 rockwell c
Material:
Material:
Material: Iron alloy 660
Material: Iron alloy 660 Material Specification:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc Specification Data:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard

NSN 5305-01-389-6372

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

