NSN 5305-01-389-6393

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-6393

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.154 inches and 0.161 inches
Head Height:
Between 0.095 inches and 0.099 inches
Width Between Flats:
Between 0.0781 inches and 0.0791 inches
Internal Drive Style:
Err-090
Thread Diameter:
0.099 inches
Width Across Flats:
Between 0.0781 inches and 0.0791 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 33.0 rockwell c and 42.0 rockwell c
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-389-6393

Machine Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A500d0