NSN 5305-01-389-6956

Shoulder Screw - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5305-01-389-6956

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| Between 0.480 inches and 0.500 inches |
| Fastener Length: |
| Between 2.725 inches and 2.755 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.543 inches and 0.562 inches |
| Head Height: |
| Between 0.240 inches and 0.250 inches |
| Shoulder Diameter: |
| 0.371 inches first shoulder and 0.373 inches first shoulder |
| Shoulder Length: |
| 2.245 inches first shoulder and 2.255 inches first shoulder |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| 0.188 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 140000 pounds per square inch |
| Hardness Rating: |
| 32.0 rockwell c and 43.0 rockwell c |
| Minimum Yield Strength: |
| 84000 pounds per square inch |
| Shoulder Shape: |
| Round first shoulder |
| Color: |
| Bronze or olive drab |
| Material: |
| Steel |
| Material Specification: |
| Fed 66 federal standard all material responses |
| Surface Treatment: |
| Zinc and chromate |

NSN 5305-01-389-6956

Shoulder Screw - Page 2 of 2



| Surface Treatment Speci |
|-------------------------|
|-------------------------|

Mil-std-171, 1.9.2.3 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.