NSN 5305-01-389-6956

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-389-6956



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.480 inches and 0.500 inches Fastener Length: Between 2.725 inches and 2.755 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.543 inches and 0.562 inches **Head Height:** Between 0.240 inches and 0.250 inches **Shoulder Diameter:** 0.371 inches first shoulder and 0.373 inches first shoulder Shoulder Length: 2.245 inches first shoulder and 2.255 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 32.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 84000 pounds per square inch **Shoulder Shape:** Round first shoulder Color: Bronze or olive drab Material: Steel **Material Specification:** Fed 66 federal standard all material responses Surface Treatment:

Zinc and chromate

NSN 5305-01-389-6956

Shoulder Screw - Page 2 of 2



Surface Treatment Specification:

Mil-std-171, 1.9.2.3 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.