--

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-7186

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.3125 inches and 0.3160 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material: Iron alloy 660
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:Passivate
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Surface Treatment Specification:
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: (q-p-35 federal specification single treatment response
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseInread Series Designator:Unrf
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qr.p-35 federal specification single treatment responseInfUnrfSpecification Data:
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:33.0 rockwell c and 42.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:80205-nas1351 professional/industrial association standard

NSN 5305-01-389-7186

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

