NSN 5305-01-389-7194

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-7194 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.230 inches **Fastener Length:** 0.620 inches **Head Style:** Knurled no. 5 **Head Diameter:** 0.500 inches **Head Height:** 0.350 inches **First Diameter From Head:** 0.160 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.350 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Concentric parallel threaded hole in threads dia. Nom. 0.138-18unc-2b Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Uns Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-389-7194

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.