NSN 5305-01-389-7980

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-7980

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.125 inches |
| Fastener Length: |
| Between 1.960 inches and 2.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.457 inches and 0.469 inches |
| Head Height: |
| Between 0.306 inches and 0.312 inches |
| Locking Feature: |
| Patch threads or pellet threads or strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| Between 0.250 inches and 0.253 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b fastener |
| Material: |
| Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or |
| steel comp xm-7 fastener |
| Material Specification: |
| Astm a493 assn standard all material responses fastener |
| Surface Treatment: |
| Passivate fastener |
| Surface Treatment Specification: |
| Astm a380 assn standard single treatment response fastener |
| Thread Series Designator: |
| Unrf |
| Specification Data: |
| 80205-nas1351 professional/industrial association standard |

N/a

Shelf Life:

NSN 5305-01-389-7980

Socket Head Cap Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0