NSN 5305-01-389-7996

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-7996

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.363 inches and 0.413 inches
Fastener Length:
Between 0.511 inches and 0.541 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.269 inches and 0.279 inches
Locking Feature:
Strip threads or patch threads or pellet threads
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp 302 fastener
Material Specification:
Ams5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unjc
Specification Data:
80205-nas1161 professional/industrial association standard

NSN 5305-01-389-7996

Close Tolerance Screw - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0