

View Online at <https://aerobasegroup.com/nsn/5305-01-389-8007>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.125 inches

Fastener Length:

Between 0.095 inches and 0.125 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.091 inches and 0.096 inches

Head Height:

Between 0.057 inches and 0.060 inches

Width Between Flats:

Between 0.050 inches and 0.051 inches

Locking Feature:

Patch or pellet or strip

Internal Drive Style:

Err-090

Thread Diameter:

0.060 inches

Width Across Flats:

Between 0.050 inches and 0.051 inches

Thready Qty Per Inch (tpi):

80

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Screw Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Locking Feature Material:

Plastic polyamide

Screw Material Specification:

Astm a493 assn standard single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Astm a380 assn standard single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0