

View Online at <https://aerobasegroup.com/nsn/5305-01-389-8007>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.125 inches

**Fastener Length:**

Between 0.095 inches and 0.125 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.091 inches and 0.096 inches

**Head Height:**

Between 0.057 inches and 0.060 inches

**Width Between Flats:**

Between 0.050 inches and 0.051 inches

**Locking Feature:**

Patch or pellet or strip

**Internal Drive Style:**

Err-090

**Thread Diameter:**

0.060 inches

**Width Across Flats:**

Between 0.050 inches and 0.051 inches

**Thready Qty Per Inch (tpi):**

80

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Screw Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Astm a493 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0