NSN 5305-01-389-8753

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-389-8753 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.596 inches and 1.750 inches **Fastener Length:** 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.375 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 316 **Material Specification:** Astm f593 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 2 type and 316 grade **Departure From Cited Document:** As modified by material

Shelf Life:

N/a

NSN 5305-01-389-8753

Socket Head Cap Screw - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.