NSN 5305-01-389-9133

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-389-9133 **Thread Direction:** Right-hand **Fastener Length:** Between 7.7 millimeters and 8.2 millimeters **Head Style:** Pan **Head Diameter:** Between 4.7 millimeters and 5.0 millimeters **Head Height:** Between 1.9 millimeters and 2.1 millimeters **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 2.5 millimeters Min. Tensile Strength (psi): 60000 pounds per square inch **Thread Pitch In Millimeters:** 0.45 **External Thread Tolerance Class:** 4g6g **Screw Material:** Steel **Screw Material Specification:** Astm a108 assn standard single material response or 66, carbon steel federal standard single material response **Screw Surface Treatment:** Zinc **Screw Surface Treatment Specification:** Qq-z-325, ty ii, class 3 federal specification single treatment response or astm b633, ty ii, class fe/zn5, assn standard single treatment response or mil-c-81562, ty ii, cl 3 military specification single treatment response **Thread Series Designator:**

Μ

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-81562 spec.