

View Online at <https://aerobasegroup.com/nsn/5305-01-389-9133>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 7.7 millimeters and 8.2 millimeters

**Head Style:**

Pan

**Head Diameter:**

Between 4.7 millimeters and 5.0 millimeters

**Head Height:**

Between 1.9 millimeters and 2.1 millimeters

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

2.5 millimeters

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Thread Pitch In Millimeters:**

0.45

**External Thread Tolerance Class:**

4g6g

**Screw Material:**

Steel

**Screw Material Specification:**

Astm a108 assn standard single material response or 66, carbon steel federal standard single material response

**Screw Surface Treatment:**

Zinc

**Screw Surface Treatment Specification:**

Qq-z-325, ty ii, class 3 federal specification single treatment response or astm b633, ty ii, class fe/zn5, assn standard single treatment response or mil-c-81562, ty ii, cl 3 military specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-81562 spec.