## NSN 5305-01-390-1933

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-390-1933

Time 101-
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.500 inches
Fastener Length:
Between 2.920 inches and 3.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
37.0 rockwell c fastener and 43.0 rockwell c fastener
Material:
Steel uns k03104 fastener
Material Specification:
Astm a574 assn standard single material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification all treatment responses fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a

## NSN 5305-01-390-1933

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0