Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-390-1935

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.875 inches	
Fastener Length:	
Between 0.845 inches and 0.8	375 inches
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.550 inches and 0.5	i62 inches
Head Height:	
Between 0.368 inches and 0.3	375 inches
Locking Feature:	
Patch threads or pellet thread	s or strip threads
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.375 inches	
Width Across Flats:	
Between 0.3125 inches and 0	.3160 inches
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
80000 pounds per square incl	1
Hardness Rating:	
80.0 rockwell b fastener	
Material:	
Steel comp 302 fastener or ste	eel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener	
Material Specification:	
Astma493 assn standard all m	aterial responses fastener
Surface Treatment:	
Passivate fastener	
Surface Treatment Specifica	ition:
Astm a380 assn standard sing	le treatment response fastener
Thread Series Designator:	
Unrf	
Specification Data:	
80205-nas1351 professional/i	ndustrial association standard
Shelf Life:	

N/a

## NSN 5305-01-390-1935

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

