NSN 5305-01-390-3413

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-390-3413

Thread Oleran
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
2.000 inches
Fastener Length:
Between 1.940 inches and 2.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.107 inches and 1.125 inches
Head Height:
Between 0.740 inches and 0.750 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.750 inches
Width Across Flats:
Between 0.625 inches and 0.631 inches
Thready Qty Per Inch (tpi):
10
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
37.0 rockwell c fastener and 43.0 rockwell c fastener
Material:
Steel uns k03104 fastener
Material Specification:
Astm a574 assn standard single material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification all treatment responses fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-390-3413

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0